



GENERAL DESCRIPTION:

Electronic faucet with proximity operation. Vandal-resistant solid brass construction. Operates on DC (battery) or AC permanent power. Water pressure range from 20 to 125 psi. Single inlet 15" flexible stainless steel hose with 3/8" compression fitting for spout connection.

PRODUCT FEATURES:

Vandal-Resistant Brass Body: Durable - Excellent in high use applications.

Power Options:

- **Battery** - Approx. 4 years with Lithium Battery CR-P2
- **Plug-In** - low voltage transformer (115 VAC supply) with 6 foot long power supply.

Easy and Flexible Installation:

3-Hole, 4" Centerset installation.
Water resistant solenoid enclosure mounts to wall.

Integrated; Easy Service Strainer:

Patented integrated strainer enclosed in removable debris cup protects the solenoid valve and aerator from debris. Perforated stainless steel strainer is low maintenance and can be easily accessed.

Temperature Mixing:

Optional thermostatic mixing valve meets ASSE 1016 performance and anti-scald requirements at 0.5 GPM. Mixing valve will connect directly to solenoid inlet and is housed in matching enclosure.

Low Lead:

Complies with CA AB1953 and VT S152.

MODEL NUMBER:

- **DC POWERED; single inlet**
 - **6055.205** with cast spout, 0.5 GPM pressure compensating, vandal-resistant spray. Battery included.
 - **6055.202** with cast spout, 1.5 GPM pressure compensating, vandal-resistant aerator. Battery included.
- **AC POWERED; single inlet**
 - **6056.205** with cast spout, 0.5 GPM pressure compensating, vandal-resistant spray. Includes AC power supply (M950169-0070A).
 - **6056.202** with cast spout, 1.5 GPM pressure compensating, vandal-resistant aerator. Includes AC power supply (M950169-0070A).
- **MULTI AC POWERED; single inlet**
 - **6057.205** with cast spout. 0.5 GPM pressure compensating, vandal-resistant spray. One power supply (sold separately) can operate up to 15 faucets in series. 10' extension cable (A922265-0070A) included.
 - **6057.202** with cast spout. 1.5 GPM pressure compensating, vandal-resistant aerator. One power supply (sold separately) can operate up to 15 faucets in series. 10' extension cable (A922265-0070A) included.
- **OPTIONAL Mixing Valve**
 - **605XTMV** Thermostatic mixing valve, flex hoses 3/8" compression 20" hose length.

RECOMMENDED SPECIFICATION

Electronic Proximity Lavatory shall feature vandal resistant all brass body with single inlet, and in-line strainer. Shall also feature a low energy use electronically operated solenoid valve and microprocessor controlled proximity sensors. Shall meet ANSI A112.18.1M and ANSI 117.1 codes. Fitting shall be American Standard Model # 6055.____, 6056____, 6057____.

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

ANSI A117.1
ASME A112.18.1
CSA B 125
NSF 61/Section 9

 **MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES**

Other Aerators Available:

Part Suffix	Description
A15LV	1.5 gpm Anti-Microbial Vandal-Resistant Laminar Flow Outlet
LV15	1.5 gpm Pressure Compensating Vandal-Resistant Laminar Flow Outlet
V10	1.0 gpm Pressure Compensating Vandal-Resistant Aerator
LV10	1.0 gpm Pressure Compensating Vandal-Resistant Laminar Flow Outlet

